

MC Series

Easy and reliable in-house processing of smaller volumes



Perfect mixing



Completely inert protection



Automatic casting



Maximum safety



Fast melting



Best metallurgy

MC 300-8

MC 300-10

MC 300-12

General Specifications

Casting quantity 22 kt
Casting quantity 18 kt
Casting quantity AG925
Crucible size
Wire
Strip
Tube
Max. temperature
Main power

3,25 kg
2,5 kg
1,75 kg
175 ccm
1 × 20; 2 × 7 mm
40 × 6 mm
35 mm
1,250°C / 1,450°C
8 KVA

5 kg
4 kg
2,75 kg
275 ccm
1 × 20; 2 × 7 mm
40 × 6 mm
35 mm
1,250°C / 1,450°C
10 KVA

7,5 kg
6 kg
4 kg
400 ccm
1 × 25; 2 × 10 mm
40 × 8 mm
45 mm
1,250°C / 1,450°C
12 KVA

Casting features

secondary cooling
die temp controller
mixing booster

○
○
○

○
○
○

○
○
○

Control features

integrated printer / RS232
system diagnose

○
◆

○
◆

○
◆

Security

cooling water security system

○

○

○

◆ STANDARD EQUIPMENT
○ OPTIONAL FEATURE
- OPTION NOT POSSIBLE