


# VPC 055 II

Powerful and economic. Automatic or manual control.



## Power

## Supreme

General Specifications		Power	Supreme
Casting quantity in 18 kt		1,600 g	2,500 g
Casting quantity in silver		1,000 g	1,600 g
Max. temperature		1,400°C	1,600°C
Flask max. size (D × H)		130 / 300 mm	130 / 300 mm
Main power		6.8 kW (3-phase)	11 kW (3-phase)
Control features	automation	automatic casting cycle	automatic casting cycle
	connect (dashboard, prgm mgmt)	-	-
	process.net (process mgmt)	-	-
Casting features	pressure-differential casting	○	○
	injection casting	-	-
	extreme overpressure (3 bar), 0.4 MPa	○	○
	flange and flangeless flask	◆	◆
	big chamber 400 mm	○	○
	crucible plus, silver quantity 3,200 gr	-	-
Metallurgy features	direct vibration technology	○	○
	mixing booster	○	○
	super silver	-	-
	super zinc	-	-
	super alloying	○	○
	protection gas regulator	○	○
Quality-control features	casting process control	○	○
	integrated printer / RS232	○	○
	sensor monitoring	○	○
◆	STANDARD EQUIPMENT		
○	OPTIONAL FEATURE		
-	OPTION NOT POSSIBLE		